



1L D5

1L D5

DIODE—SHARP-CUTOFF PENTODE

GENERAL DATA

Electrical:

Filament, Coated:

Voltage. 1.4 dc volts

Current. 0.05 amp

Direct Interelectrode Capacitances:^o

Pentode Unit:

Grid No.1 to Plate . . 0.18 μf

Input. 3.2 μf

Output 6.0 μf

^o With external shield connected to negative filament terminal.

Mechanical:

Mounting Position. Any

Maximum Overall Length 2-25/32"

Maximum Seated Length. 2-1/4"

Maximum Diameter 1-3/16"

Bulb T-9

Base Lock-in 8-Pin

Basing Designation for BOTTOM VIEW 6AX

Pin 1—Filament (+)

Pin 2—Pentode

Plate


Pin 3—Pentode

Grid No.2

Pin 4—Diode Plate

Pin 5—No

Connection



Pin 6—Pentode

Grid No.1

Pin 7—No

Connection

Pin 8—Filament (-),

Pentode

Grid No.3

Plug —Base Shell

PENTODE UNIT AMPLIFIER — Class A₁

Maximum Ratings, Design-Center Values:

PLATE VOLTAGE. 110 max. volts

GRID-No.2 (SCREEN) VOLTAGE 50 max. volts

Typical Operation and Characteristics:

Plate Voltage. 45 90 . . volts

Grid-No.2 Voltage. 45 45 . . volts

Grid-No.1 Voltage. 0 0 . . volts

Plate Resistance (Approx.) 0.9 0.75 . . megohm

Transconductance 550 575 . . μmhos

Plate Current. 0.55 0.6 . . ma

Grid-No.2 Current. 0.12 0.1 . . ma

DIODE UNIT

The diode is located at the negative end of the filament and is independent of the pentode unit except for the common filament.

OCTOBER 15, 1947

TUBE DEPARTMENT
RADIO CORPORATION OF AMERICA, HARRISON, NEW JERSEY

DATA